



TECHNICAL SPECIFICATION CARGO 30 TON SEMI-TRAILER

DIMENSIONS

Overall Length: total 12.000 mm;

Overall Width: total 2.500 mm;

Frontwall Height: 1.500 mm

Payload: 30 Tons

Side and rear Boards, in ribbed sheet steel, with height 800 mm, thickness 2.5 mm, removable and folding, divided in section

STEEL CHASSIS

2 Automatic welded main beams linked by steel struts in profile to form the platform.

3,5" King pin detachable from below

ROLLING EQUIPMENT

Reinforced mechanical suspension with semi-elliptical leafs

2 Rigid axles of 12 ton Dmix

Drum brakes

8 Tyres + 1

BRAKING SYSTEM

Two lines with sensitive valve

Parking brake.

KING PIN

3 ½ Inch King Pin from below

LANDING GEAR

Mechanically operated with universal base plate

2 Speeds telescopic reinforced.

LIGHTING AND SIGNALLING

24 volts type

Combined double rear lights including stop light, directional indicators, number plate light (on one side only),

Triangular reflectores, 2 at rear,

Round reflectors,



Dmix International A.S.R.L.S.

BODY EQUIPMENT

6 mm Checkered steel floor.
Mechanical rear feet supports.
Fixed and reinforced Front board 1500mm height;
Winch for cord-tightening on side and rear with hook;

OTHER EQUIPMENT

20 l Drinking Water tank
Tools box
Basket type Spare wheel support
Mudguards on tyres with splash boards
Heavy duty rear bumper

PAINT WORK

Shot blasting, primary and 2 components final anticorrosion painting

Dmix International A.S.R.L.S.

HEADQUARTER: Viale Enzo Paolo Tiberi n° 8, 06124 PERUGIA (PG) **WORKSHOP:** Via Grecia N° 16, Trestina 06012 CITTA' DI CASTELLO (PG)

C.F./P.IVA: 03610350542 **REA:** PG301726 **E-mail:** international@dmixsrl.com, dmixinternationalsrls@gmail.com

Codice Fatt.Elett.: USAL8PV **PEC:** dmixinternational@pec.it **WEB:** www.dmixinternational.com