



Bi-directional Rigid frontal dumper, hydrostatic, 6 cu.m heaped, 8000 kgs capacity









TECHNICAL SPECIFICATIONS

DIESEL ENGINE	Stage IIIA / Tier 3	
Model :	PERKINS series 1,104	
Type :	Turbo	
Total displacement, no Cylinders :	4,400cc - 4 in line	
Injection :	mechanical control with direct injection	
Cooling :	air water, dry air fi Iter	
Maximum power :	74 kW (101 Hp)	
Adj. power :	70 kW (2,200 rpm)	
Maximum torque :	392 Nm a 1,400 rpm	
Alternator:	12 V - 65 A	





ELECTRIC SYSTEM

Battery: 12 V - 132 Ah (600 A) Road light system, rear working lights. COBO Made in Italy

4X4 FOUR-WHEEL DRIVE

Hydrostatic "automotive" transmission with variable displacement pump and variable displacement hydraulic motor with electro-hydraulic control, and reverse gear control on the steering wheel. Mechanical gearbox for "working speed" and "road transfer" speed.

Hydraulic motor and pump Bondioli&Pavesi Italy

SPEED

Working speed from 0 to 12 km/h Road transfer from 0 to 25 km/h

AXLES AND WHEELS

Brand Comer Made in Italy

Front load-bearing, oscillating $(\pm 7^{\circ})$ and steering with planetary reduction gears on the wheel hubs.

Rear load-bearing and steering with planetary reduction gears on the wheel hubs and directly fl anged gearbox.

Front and rear tyres: 405/70-20 PR14 Brand: Mitas or BKT



BRAKES

Brake pump Brand: SAFIM made in Italy Internal oil-bath disc service and emergency brakes acting on the 4 wheels, activation with pump on independent dual circuit. Mechanic type parking brake, with internal oil-bath discs.

STEERING

Brand Bondioli e Pavesi or MS Hydraulic

Assisted by means of power steering on 4 steering wheels; steering selection device for: 2 steering wheels, 4 steering wheels - crab steering.

EQUIPMENT HYDRAULIC SYSTEM


Gear pump

Aluminium heat exchanger for hydraulic oil cooling.

Pressurised closed-circuit intake with oil filter replaceable from the outside.

Brand Bondioli e Pavesi made in Italy

DUMP BODY



CAB

Cabin with glass on front, rear and left side accordance with ROPS FOPS.

180° pivoting driving post. Anatomic seat with flexible suspension and height adjustment, seat belts.

Driving and equipment controls with ergonomic arrangement.

SERVICE REFILL CAPACITIES

Fuel tank:	90 litres
Total hydraulic system capacity:	180 litres
Engine oil:	9 kg

WEIGHTS

Operating weight	5,590 kg
Max gross weight:	13,590 kg
load-carring capacity:	8,000 kg

The picture can shows optional accessories. Technical specifications and dimensions are only for information and not binding for the producer. In accordance with our policy of continual improvements, we reserve the right to modify such specificationswithout notice.